

Amendments to the Claims

The following listing of claims will replace all prior versions, and listings, of claims in the instant application:

Listing of Claims:

1. (Currently Amended) A composition comprising Component A and Component B;
 wherein Component A comprises: gypsum, an alkaline first polymer, an alkaline agent selected from an amine and alkaline earth base, and a hydration inhibitor selected from a polymer and copolymer of polycarboxylic acid;
 wherein Component B comprises: a second polymer, a filler, and an activator; and
 wherein both Components A and B are dispersed in an aqueous medium.
2. (Canceled).
3. (Previously Presented) The composition of claim 1 wherein the volume ratio of Component A to Component B is from 95:5 to 5:95.
4. (Previously Presented) The composition of claim 1 wherein Component A comprises: 20-50 wt% alkaline first polymer; 50-80 wt% gypsum, 0.05-1.0 wt% alkaline agent, and 0.1-2.0 wt% hydration inhibitor, based on the total weight of Component A.
5. (Previously Presented) The composition of claim 1 wherein Component B comprises: 20-70 wt% second polymer; 30-50 wt% filler and 0.1-6.0 wt% activator, based on the total weight of Component B.
6. (Previously Presented) A method of forming a polymer-modified gypsum comprising
 forming Component A and Component B; wherein Component A comprises: gypsum, an alkaline first polymer, an alkaline agent selected from an amine or alkaline earth base, and a hydration inhibitor selected from a polymer and copolymer of polycarboxylic acid; wherein Component B comprises: a second polymer, a filler, and an activator; and wherein both Components A and B are dispersed in an aqueous medium; and
 admixing Component A and Component B.
7. (Original) The method of claim 6 further comprising applying said admixture to a substrate.
8. (Original) The method of claim 7 wherein the substrate is the excavated rock surface of a subterranean mine.
9. (Original) A polymer-modified gypsum formed by the method of claim 6.
- 10-12. (Canceled).